





TRIGGER GUNS

Ideal for fabricating custom spray guns. Make your own or let us design and manufacture the perfect spray tool for your job.

	MAX 18 GPM	MAX 700 PSI	#23.208.84 Anodized aluminum trigger valve has 1/2" female inlet and outlet ports. UDOR trigger valve provides an excellent means for fabricating custom spray guns.
	MAX 18 GPM	MAX 700 PSI	#15.0003.13 Reinforced polypropylene trigger valve has 1/2" female inlet and outlet ports. Provides an excellent means for fabricating custom spray guns.

TRIGGER GUNS - 23H



1000 PSI
5 GPM
200°F

The 23H high pressure GunJet® features a strong aluminum alloy handle with a comfortable trigger grip. A trigger guard helps prevent accidental discharge. 23H guns are designed so that only the inlet body, tip retainer and orifice tip touch the liquid sprayed.

Model 23H GunJet® operates at pressures from 250 to 1000 PSI (17 to 70 bar) and pro-

vide flow rates up to 5 GPM (19 l/min). Liquid temperatures up to 200°F (93°C) can be tolerated. The 23H gun has a 1/4" NPS (M) inlet connection.

23H GunJet® offers a nickel plated brass inlet body and tip retainer, a Teflon valve seat and a stainless steel stem with brass guide.

11/16"-16 THD outlet. Use with UniJet® spray tips.

TRIGGER GUNS - 30



1500 PSI
5 GPM
200°F

The Model 30 GunJet® is a heavy-duty impact resistant spray gun with a sturdy Nylon handle and trigger guard. The 30 gun is a high pressure gun which remains responsive and easy to operate even at maximum flow and pressure conditions. The light trigger pull provides positive control. The heat resistant handle remains comfortable even at high temperatures. A special trigger lock feature locks in the "off" position to prevent accidental discharge and retracts flush

into the handle when the gun is in use. The 30 gun has a 1/4" NPT (F) inlet connection.

Model 30 spray guns feature a Buna-N stem seal, a Teflon valve seat and a stainless shut off needle. The valve body is forged brass.

11/16"-16 THD outlet. Use with TeeJet® spray tips or extensions.

GUNJET® SPRAY GUNS



Type 43LC-1/2 & 43HC-1/2 and 43LC-3/4 and 43HC-3/4 GunJet® Spray Guns

Types 43LC-1/2 and 43HC-1/2 have 1/2" NPT (F) outlet connections. Type 43LC-3/4 and 43HC-3/4 have 3/4" NPT (F) outlet connections. Inlet connections are 1/2" NPT (F).

WASH GUNS - 60



2500 PSI
6 GPM
300°F

Model 60 GunJet® operates at pressures up to 2500 PSI (175 bar) and provides flow rates up to 6 GPM (23 l/min.). Liquid temperatures up to 300°F (150°C) can be handled. The 60 gun has a 3/8" NPT (F) inlet connection.

11/16"-16 THD outlet. Use with UniJet® spray tips.



HIGH PRESSURE WASH GUNS - PW4000



4000 PSI
10 GPM
300°F

The **Model PW4000 GunJet®** is a high pressure spray gun that offers exceptional operator comfort and control, even at maximum flow and pressure conditions.

A bottom pivot trigger reduces operator fatigue by making trigger pull easier. The shutoff valve is located in the base of the handle, concentrating heat away from the operator's hand and slowing heat build-up.

The PW4000 is easy to maintain because

the packing screw is easily accessed at the base of the handle. There is no need to separate handle halves when rebuilding the gun. It operates at pressures up to 4000 PSI (275 bar) and provides flow rates up to 10 GPM (38 l/min.). Liquid temperatures up to 300°F (150°C) can be handled. 1/4" and 3/8" NPT inlet and outlet connections are available.

Model PW4000 GunJet® features durable polycarbonate handles.

PRESSURE WASHING ACCESSORIES

We stock a wide variety of TeeJet® nozzles in brass and stainless steel. Please call for details.

Wands:



1/4" Male NPT ends with insulated handgrip.

#MG-24	24"
#MG-36	36"
#MG-48	48"

Hoses:



Single wire braid hose assembly. 3000 PSI operating pressure, 3/8" I.D. with hose bend restrictors.

Please specify length and fittings (rigid or swivel).

THERMOPLASTIC FOG NOZZLE



Adjustable from straight stream to fog. For use with water up to 100 PSI.

Size	Thread	Part No.
3/4"	GHT	FNB75GHT
1"	IPT	FNB100S
1"	NST	FNB100NST
1 1/2"	IPT	FNB150S
1 1/2"	NST	FNB150NST

BRASS ROLLOVER VALVE



Brass Rollover Valve with Viton O-rings allow user to switch between two nozzles with a simple twist. Perfect for precise, low volume applications.

Rollover Gun Assembly	#AA30-1/4ASSY
Rollover Valve Only	#4990390

See page 89 for available extensions.